



PromaxVac.

Manufacturer of Food Processing & Packaging Machinery



QUALITY YOU CAN TRUST!

Head Office

1915 E. Acacia Street, Ontario, CA91761, USA
Tel: 1-909-923-3888 Fax: 1-909-923-3588
E-mail: sales@promarksvac.com

East Coast Office

JVR INDUSTRIES INC.
100 West Drullard Ave Lancaster NY14086, USA
Tel: 1-716-897-4309 Fax: 1-716-897-4731
www.jvrinc.com

Asia Office

Foodmax Machinery Co., Ltd.
No 9 Jhongsing Road, Chia-Tai Industrial Area, Chia-Yi, 61252, TAIWAN
TEL: 886-5-2383788 FAX: 886-5-2385388
E-mail: sales@foodmax.us

<http://www.promaxvac.com>

TCM Series - Bowl Cutter

- Suitable for mixture minced meat, minced fish and ham with seasoning.
- Suitable for soy protein and gluten protein combine water or oil for emulsify.
- Suitable for meat and vegetable cutting.
- Change for obtuse knife to dismantling tissue of soy protein or gluten protein to filose.

Standard Features:

- 6 Knives for High-Quality Production
- Two Speed Bowl Motor Control
- Variable Speed on Cutting
- Heavy Duty Stainless Steel Bowl Construction
- Safety Bowl Break Mechanism
- Product Discharge system
- Digital Temp Display
- Products Unloader
- Reverse blade rotation (for mixing) (model above TCM-130)
- Safety sensor for lid.



TCM-65

Options

- Variable Motor Drive for Bowl
- Voltage(TCM-200.330 need to be higher than 380V)

Technical Data	TCM-65A	TCM-130	TCM-200	TCM-330
Bowl-capacity	65 liter / 14.3 gal	130 liter / 28.6 gal	200 liter/52.8 gal	330 liter / 72.5 gal
Working ability	43kg/once	100kg/once	140kg/once	240kg/once
Motor rating knives	25HP	40HP	75HP	100HP
Motor rating bowl	0.5HP	2HP	5HP	7.5HP
Motor rating discharge	0.5HP	2HP	3HP	3HP
Knife rotation	0~4200rpm	0~4200rpm	0~4200rpm	0~3000rpm
Bowl rotation	10/20rpm(60Hz) 8/17 r.p.m. (50Hz)	9.5/19 r.p.m. (60Hz) 8/16 r.p.m. (50Hz)	10/20 r.p.m. (60Hz) 8/17 r.p.m. (50Hz)	9.5/19 r.p.m. (60Hz) 8/16 r.p.m. (50Hz)
Electric power supply	220V / 3ph / 50/60Hz	220V / 3ph / 50/60Hz	380V/3ph/ 50Hz/60H	380V / 3ph / 50/60Hz
Dimension	1460x1310x1340(mm) 57.4" x51.5" x52.7"	2200x1900x1350(mm) 86.4"x74.8"x53"	2768x2368x487mm	3100x2500x1590(mm) 122"x98.4"x62.5(mm)
Weight	900Kg (1980 lbs)	2900Kg (6380 lbs)	4000kg(8800lbs)	4500Kg (9900 lbs)

All specifications are subject to change without notice.

Ask Us about our quality products !